

ETOZ SEMI SYNTHETIC ENGINE OIL

Product Data Sheet

Description :

ETOZ Semi Synthetic Engine oil SAE 10W40 is a high quality semi-synthetic multi grade and multipurpose gasoline engine oil. It meets and exceeds performance levels of SJ, SL and SM lubricants and is specially formulated for use in gasoline and diesel powered passenger cars, vans and light trucks of almost all makes of American, European and Japanese vehicle.

It is formulated from highly refined conventional base oils together with a multifunctional additive package. It has very low volatility and evaporation loss and offers high resistance to oxidation, and reduces fuel consumption.

Standards:

Meet or surpasses the requirements of the following classifications or standards:

1. API SM / CF

Benefits:

- Excellent control of corrosion and piston deposits in gasoline engines.
- Excellent sludge and oxidation resistance.
- Low volatility and evaporation loss.
- Resistance to deterioration, especially that caused by oxidation.
- Superior cold start performance and efficient cold engine lubrication.
- Reduce fuel consumption.

Certificate of Analysis :-

	SAE	Unit	10W/40
Density@ 15 °C	ASTM D 4052	kg/L	0.8616
Kinematics Viscosity			
@ 40 °C	ASTM D 7042	cSt	79.71
@ 100 °C	ASTM D 7042	cSt	12.30
Viscosity Index	ASTM D 7042	-	151.1
Total Base Number	ASTM D 2896	mgKOH/g	7.64
Flash Point	ASTM D 92	°C	214
Pour Point	ASTM D 97	°C	-9

* Values Shown Here Are Typical And May Vary.

Precautions

ETOZ Engine Oil is manufactured from high quality petroleum base stocks, blended with quality additives. As with all petroleum products, good personal hygiene and careful handling should always be practiced. Avoid prolonged contact to skin, splashing into eyes, ingestion or vapor inhalation.